Jax London presents:

SPRING BOOT

by Michael Simons

BASICS

What exactly is Spring Boot?

The term „Microservices Framework" is often used when talking about Spring Boot.
This is only partly true: Spring Boot is suitable for small services as well as for monolithic applications. These services or applications can be pure Web APIs or web applications, command line applications or batch processes. Last but not least, Spring Boot orchestrates the Spring Framework. Support for different runtime environments, cloud infrastructure ready, especially Dependency Injection and aspect oriented programming. With these, building blocks become higher value components, that are ready for production. These may include transactions, security, and more. Spring Boot starts a Spring Container and configures - depending on the dependencies on the classpath (see also Maven/Gradle) and "corresponding" further modules.

Are there any alternatives?

Coming from the enterprise Java world, WildFlyWeb must of course be mentioned. Further exciting developments are Quarkus and Micronaut. These developments are intriguing for several reasons: Most of the cloud related decisions made by Spring Boot, starting with version management up to declarative configuration, health endpoints, and even project generation, are made at compile time. Quarkus and Micronaut have started a development that focuses on faster starting services, and even boot quickly to ensure an elastic infrastructure.
Naturally, the teams behind Spring Boot also take up these issues.

@SpringBootApplication

Everything starts with the annotation **`@SpringBootApplication`**.
It marks a single class as the central entry point into a Spring Boot application.

`@SpringBootApplication` is a composite annotation, consisting of:

- **`@SpringBootConfiguration`** (alias for **`@Configuration`** with **`proxyBeanMethods = true`**)
- **`@EnableAutoConfiguration`**
- **`@ComponentScan`**

The last two annotations are the most important ones: Firstly, they switch the search after Spring components (including **`@Component`**, **`@Service`**, **`@Controller`** and others) on for further mechanisms.
Three rules apply to the **`@SpringBootApplication`** like the first boot should be considered hard rules:

1. The Class does not need any further annotations. All other, domain oriented configurations should be on corresponding **`@Configuration`** classes.
2. A Class annotated with **`@SpringBootApplication`** should never be included in the root package (i.e. without **`package`** declaration). In this case, Spring would jump all classes starting from the root package and try to find classes with known annotations.
3. Although it is possible to apply other methods annotated with **`@Bean`** in this class, it should be omitted for reasons of clarity. The preferred place for this is the **`@Bean`** method.

The following listing shows what an "ideal" Spring Boot **`Main`** class looks like:

Standard Spring Boot main Class

```
import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class MyApplication {

    public static void main(String[] args) {
        SpringApplication.run(MyApplication.class, args);
    }
}
```

VERSION MANAGEMENT AND ADMINISTRATION OF DEPENDENCIES

Version management and the administration of dependencies are essential functions of Spring Boot, even if they are usually extremely inconspicuous and are often unnoticed. Spring Boot, Maven and Gradle are used, that this provides mechanisms for application developers to do this.

Developers can create dependencies without declaring versions. Managed dependencies are published together with their versions under **Managed Dependency Coordinates**. Spring Boot is automatically tested with these versions.

If in certain cases it is mandatory to use a different version, it should not be declared manually but the **`properties mechanism`** used to overwrite the version. First, the name of the corresponding property is determined in the **Version Properties** list and then set.

Maven

Define a property with the appropriate name and version:

```
<properties>
    <neo4j-ogm.version>3.2.10</neo4j-ogm.version>
</properties>
```

Gradle

Create a **`gradle.properties`** in the project and define properties as follows:

```
neo4jVersion = 3.2.10
```

Neo4j OGM, a mapping framework for the graph database Neo4j, has only been used here as an example.

WHAT IS A STARTER?

Starter is the second important pillar of Spring Boot. They usually consist of a starter and an autoconfiguration module. The Starter Modules provides all necessary dependencies, the **Autoconfiguration** Module can configure the Spring Container, Spring Module, and other technologies depending on various conditions.

These conditions include the presence or absence of classes in the classpath, the presence or absence of specific bean definitions, environmental variables, properties, and more. These conditions are defined by specifical **`@Conditional`** classes that are defined using the methods described in Annotation **`@EnableAutoConfiguration`**.

A starter is added to a project by declaring the corresponding dependency. So that the corresponding configuration classes are automatically included, Spring Boot scans through the entire classpath, a service loader mechanism similar to the Java Service Provider SPI is used.

MANUAL (SPECIFIC) CONFIGURATION

Properties

The Spring Boot Guide lists over 1000 properties that an application configuration can be: **Common Application Properties**. Of course, these properties are not always available. They only appear - apart from the Core Properties and some others - when the corresponding starter is used. Spring Boot provides a mechanism for developers to define their own application specific configurations. All are centrally documented, and the dedicated Spring configuration classes can appropriately react to changes. Properties can originate from files (**`application.properties`** or **`application.yml`**), from environment variables or program arguments. You can use different profiles that can be validated and much more. Special data types such as URLs, memory sizes, lists etc. are converted correctly.

@ConfigProperties

Classes that are annotated with **`@ConfigProperties`** are Spring components that affect the contents of the Spring container their properties are bound to. Setters and return values of the methods are also used as bean a part of the Spring container. By default, the beans are named FooBar.

These additional beans influence the automatic configuration of other beans. For example, a bean of type DataSource is expected. If so, starter can be completely "switched off" or take only what is true for a part of its configuration, because the non-specific bean already does that.

This can sometimes lead to irritation. In case of doubt, looking at a reference, in particular the annot **Autoconfiguration Classes**.

-IMPORTANT FEATURES-

TEST SUPPORT

The starter under the coordinates **`org.springframework.boot:spring-boot-starter-test`** brings all necessary dependencies to use with JUnit Jupiter, wrote Assert, and Mockito.



All the annotations mentioned are internally linked with **`@ExtendWith({SpringBootApplicationClass})`** annotated. Further Jetzt annotations are not necessary for standard application cases.

Important annotations are here:

- **`@SpringBootTest`** starts a complete Spring boot application. Alternatively, a Spring Web is on the class path, a **`MockWebServer`** is used by default.
- **`@CountDown`** only configures the support for JSON properties (configuration of the mapper, time zone, formatting, etc.)
- **`@WebMvcTest`** only configures the web layer, services and repositories that must be mounted. A **`MockMvc`** instance is automatically created for testing.
- **`@WebFluxTest`** configures the reactive web layer of the class **`WebTestClient`** is ready for use.
- **`@DataJdbcTest`** configures the database layer for the specified persistence layer. This can be JDBC, JOOQ, Neo4j, Redis, Mongo or LDAP. Tests roll transactions automatically. If necessary, an in-memory version of the respective store is used.

Starting from the annotated test class, the path specified in the class path after the **`src/main/resources/application.properties`** or **`application.yml`** is searched. The configuration is then searched for the profile selected according to the test class.

Tests can be executed by classes that begin with **`IntegrationTest`** or end with **`IT`**. Maven Failsafe Plugin **`failsafe:integration-test`** takes the advantage of being the added automatic Spring Boot configuration for tests and not - like **`JUnitTestSuite`** classes in the Test path - replaced.

If the test dists are used, additional **`@DataJdbcTestIntegrationTest`** annotation is used. Its **`@AutoConfigureWebTestClient`** can be used to add further aspects.

ACTUATOR

The term **Actuator** includes Spring Boot's "Production Ready Features". These are metrics and health, audit, and HTTP tracing. Spring Boot Actuator is defined by the dependency **`org.springframework.boot:spring-bootstarter-actuator`**.

All endpoints - except for **`Shutdown`** - are activated by default and, with a few exceptions, JMX is exposed via JMX. To make them available via HTTP, they must be exposed via **`management.endpoints.web.exposure.exclude=*`** or **`management.endpoints.web.exposure.include=*`** and an activated editor by setting the **`*`** or by cases (see **Endpoints**).

Endpoints are only secured if Spring Security is on the classpath. All web endpoints are available by default under **`/actuator/{id}`**, for example: **`/actuator/health`**. Some endpoints may only provide a subset of available information when no user is logged in.

Metrics are available under **`/actuator/metrics`**. Custom endpoints, health, and application information can be provided. Database starters offer provide additional connectivity information. For example, Neo4j looks like this:

Example of health information using curl:

```
{
  "status": "UP",
  "details": {
    "neo4j": {
      "status": "UP",
      "details": {
        "server": "Neo4j/4.0.0Enterprise(127.0.0.1)",
        "database": "ok",
        "connection": "ok"
      }
    }
  }
}
```

LOGGING

Logging can be performed uniformly for SfB, Log4j and other locales under can be configured with the prefix **`logging.*`**. **`logging.file`** and **`logging.pattern.*`** define properties for logging. Setting **`logging.level.LOGGERNAME`** the default level of the corresponding logger can be configured.

Using prop.group **`GROUPNAME=LIST OF LOGGERS`** logging groups can be defined, independent of the library used. This can then be used as described above and can be configured with **`logging.level.GROUPNAME`**.

PROFILE

Both properties files and configuration classes can be profiled. Properties files are named **`application-{profile}.properties`** and are loaded from **`application.properties`** (**`application-PROFILE`**). When starting the application via a plant parameter (**`--spring.profiles.active=PROFILE`**) or via the entry determined in the standard configuration under the **`key spring.profiles.active`** of which profiles are active.

APPLICATION PACKAGING

Both Maven and Gradle have plug-ins available that are automatically included in the corresponding build descriptor when the application is generated. These plug-in generate an executable **JAR** or **WAR** file during the package phase. This archive contains the actual application code and all dependencies.

If this does not fit in the planned deployment scenario, a different layout can be used. The corresponding Maven or Gradle plugins support this by called **`spring-boot:repackage`**. layout. You can use **JAR, WAR, ZIP, DIR,** or **NONE. DIR** is one option for layers of Docker Images.

In Spring Boot 2.3, optimized build packs are available. These build packs rally various best practices for creating Docker images for Spring Boot applications.
With an mvn **`spring-boot:build-image`** or Gradle **`bootBuildImage`** you can generate an image. In this case, the new layout **LAYERED JAR** is used. It pushes libraries into a separate Docker Layer, which is usually much more stable than the application itself.
In speed up image creation and keep deploy details small for new deployments.

-MISC-

LAZY INITIALIZATION

Spring boot applications can work with Lazy Initialization. This means that beans are created as late as possible, namely when it is needed will be. This will speed up application start in some cases, but can also lead to late errors. Whose bean errors are incorrectly configured but are not needed directly at the start.

If it is ensured that the application is configured correctly, the feature for an application is activated via **`spring.main.lazy-initialization=true`**.

DEVELOPER TOOLS

Of course, Spring Boot itself is a "development tool". But there is also an optional SpringBoot module called **`org.springframework.boot:spring-boot-devtools`**.

Developer Tools changes the default values of some configuration properties during development time. For example, most caches are disabled, so that changing data or templates these changes become immediately visible.

The most striking feature is an automated restart after class changes. All necessary parts of the application that are affected by a change are completely restarted. A delta in the configuration is logged.

This should only be declared as an optional dependency. On a packaged application, which is started with **`java -jar`**, the Developer Tools have no effect.

STARTSPRING.IO

Josh Long, Developer Advocate at VMWare Tanzu (formerly Pivotal), likes to refer to start.spring.io as the best place on the Internet and a panacea for various ailments.

This may be exaggerated, but the **Spring Initializr** is nevertheless a very practical application. In a form where you enter the basic data of a new service, you must enter:

- Project Coordinates
- Name
- Language (Java, Kotlin or Groovy)
- Java version and Spring Boot version
- and of course the dependencies

The result in the download is a zip file containing a Build Descriptor, a **`bootapp`**, **`.bin`**, a basic test, GIT Ignore and a README with information about dependencies and build system.

Spring Initializr can also be used via **`cURL`**, so it can be used in automated deployments. Of course, there major IDEs also take advantage of this functionality: In IDEA, NetBeans, and Eclipse you can generate new Spring Boot projects directly from the IDE using the Initializr.

As of 2020, the application is no longer comparable with the initial version of 2013/2016. Since then, there is now a preview functionality, a "share" link, and much more. On top of that, the open source software based on Spring Boot is available. Now that **`bootapp`** or **`initializr`** is available, the initializr can be adapted for your own purposes and can be used in your own setups.

HOW-TO-GUIDES

Under **"How-to-Guides"**, the Spring Boot team publishes answers to "How-do-I..." questions. These range from configuration suggestions and the adaptation or the selection of the embedded server up to database access, batch processing, and much more.

Jax London
jax.de
Big Data Minds & Software Craftsmanship
Big Data Minds & Software Craftsmanship, Thomas Bonfort Strasse